



DECON
Technologies

Global Sourcing Partner Supply Chain Engineering & Marketing



INDUSTRIAL

Pressure Gauges

our products



INDUSTRIAL PRESSURE GAUGE

MERCURY TEMPERATURE GAUGE

BI-METAL TEMPERATURE GAUGE

PRESSRE GAUGE ACCESSORIES

DECON
TECHNOLOGIES

2020

Weather Proof Gauges

SIZE : 2",2 1/2",4",6",10"
 SS Casting, Brass, SS Internal
Accuracy : ± 1%
Range : 1 to 1000 kg/cm²
 0 adjustable pointer B.O.D



Electric Contact gauges

SIZE : 4",6"
 SS Casting, Brass, SS Internal
Accuracy : ± 1%
Range : 1 to 1000 kg/cm²



Glycerine Filled Gauges

SIZE : 2",2 1/2",4",6",10"
 Sheet metal Casting, Brass Internal
Accuracy : ± 1%
Range : 1 to 1000 kg/cm²

Differential gauges

SIZE : 4",6"
 Built in over range Equalising valve
 External 'O' adjustment
 SS casing SS Internals
Accuracy : ± 1.5% FSD
Range : 400 mm WC to 25kg/cm²



Sealed Diaphragm Gauges

SIZE : 2",2 1/2",4",6",10"
 Sheet metal Casting, Brass Internal
 SS/PTFE coated contact parts
 Screw and flanged connection
Accuracy : ± 1%
Range : 1 to 1000 kg/cm²



Draft Gauges

SIZE : 6",8"
 SS Casting, Brass, SS Internal
Accuracy : ± 1.5%
Range : 50mm WC to 1000mm WC



Schaeffer Diaphragm Gauges

SIZE : 4",6"
 SS Casting, Brass, SS Internal
Accuracy : ± 1.5%
Range : 1 to 28 kg/cm² & compound



Test Gauges

SIZE : 6",10"
 Aluminium Die cast weather proof case
 SS case, SS internals
Accuracy : ± 0.25% or 0.5% FSD
Range : 1 to 1000 kg/cm²



Pressed Steel Gauges

SIZE : 1 1/2",2",3",4",6",8",10"
 Sheet metal Casting, Brass Internal
Accuracy : ± 2%
Range : 1 to 700 kg/cm²

Compact Capsule Gauges

SIZE : 2 1/2",4",6"
 SS Casting, Brass, SS Internal
Accuracy : ± 2%
Range : 100 to 7000 kg/cm²
 WC/25 mbar to 400 mbar



Temperature gauges

SIZE : 2 1/2", 4", 6", 10"
 Mercury in steel
 Accuracy : ± 1%
 Range : 38 to 600 degree C
 Type : Rigid Stem & Capillary
 MOC : MS/SS304/SS316/Copper



❖ BI-METAL TEMPERATURE GAUGES

BI Metal Gauge

SIZE : 1 1/2", 2 1/2", 4", 6"
 BI Metallic
 Accuracy : ± 2%
 Range : 38 to 600 degree C



GAUGES ACCESSORIES

Gauge Saver

SS / Brass
 1-400 kg/cm²

Snubber / Damper

U/Q Type
 SS/MS Plated
 1-420 kg/cm²

Needle Valve

SS / Brass
 1-700 kg/cm²

Gauge Cock

SS / Brass
 SS/MS Plated
 1-420 kg/cm²

Syphone Tube

SS / Brass

Thermo well

SS / Brass
 MS Plated



✉ : sales@deconconnect.com
 ☎ : +65 9782 1432

Scale

Pointer

Spring

Tube section

Bourdon tube

Rack

Pivot